

1009

Modwash



54

CONSTRUCTION & DESIGN

- Recessed LED fixed wall wash downlight
- Constructed in die cast aluminium alloy and finished in satin white or matte black powdercoated paint
- Fixed recessed LED wall washer for lighting vertical displays
- Designed with minimal trim width to visually integrate within planar ceiling
- Clear tempered glass providing IP44 protection
- Ideal for spaces such as foyers, hotels, corridors, displays, function rooms and residential

TECHNICAL PERFORMANCE


- 8W, 13W or 22W total system power consumption with overload and short circuit protection
- > 65,000 hours lifespan (L70)
- Premium quality Japanese LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K, and 5K colour temperature with low colour shift over time






OPTICAL & THERMAL PERFORMANCE

- Reflector and customised heatsink provides premium optical and thermal performance
- Efficient optical control in various beam angles with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM





- Supplied complete with remote leading and trailing edge mains dimmable driver, also compatible with a range of dimming systems
- All drivers come with power cord and plug
- Quick connect driver
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60Hz



 23° FIXED TILT	Weight (kg) 0.3	3K and 4K CRI >85	5K CRI >75	 78					IP44
--	---------------------------	----------------------	---------------	--	---	---	---	---	------

TOTAL SYSTEM POWER CONSUMPTION = 8W /13W /22W



CODE ORDERING GUIDE: PRODUCT CODE /DIMMING SUFFIX (if required) – COLOUR SUFFIX
 Example: 1009-SP-3K-8W-01 or 1009-SP-3K-8W/DALI-01

WATT	COLOUR TEMP.	 24° SP	 36° FL	 47° WFL	 55° VWFL	HOT LED LUMENS
		PRODUCT CODES				
8W	3K	1009-SP-3K-8W	1009-FL-3K-8W	1009-WFL-3K-8W	-	828
	4K	1009-SP-4K-8W	1009-FL-4K-8W	1009-WFL-4K-8W	-	870
	5K	1009-SP-5K-8W	1009-FL-5K-8W	1009-WFL-5K-8W	-	888
13W	3K	1009-SP-3K-13W	1009-FL-3K-13W	-	1009-VWFL-3K-13W	1519
	4K	1009-SP-4K-13W	1009-FL-4K-13W	-	1009-VWFL-4K-13W	1607
	5K	1009-SP-5K-13W	1009-FL-5K-13W	-	1009-VWFL-5K-13W	1646
22W	3K	1009-SP-3K-22W	1009-FL-3K-22W	-	1009-VWFL-3K-22W	2414
	4K	1009-SP-4K-22W	1009-FL-4K-22W	-	1009-VWFL-4K-22W	2584
	5K	1009-SP-5K-22W	1009-FL-5K-22W	-	1009-VWFL-5K-22W	2618

DIMMING OPTIONS: ADD SUFFIX AFTER THE CODE

		8W	13W	22W
/DALI	Dali Dimming	✓	✓	✓
/DSI	Digital Dimming	✓	✓	✓
	Switch Dim	✓	✓	✓
/AD	Analogue Dimming 1-10V	✓	✓	✓
	Leading & Trailing edge mains dimming	STANDARD	STANDARD	STANDARD

TRIM COLOUR OPTIONS: ADD SUFFIX AFTER THE CODE

- 01  Satin White
- 06  Matte Black