

1057-2L

Riga 2



CONSTRUCTION & DESIGN

- Recessed LED adjustable downlight
- Housing and trim is constructed in steel and the trim is finished in satin white, matte black or bright silver powdercoat paint
- Recessed black housing creating a dynamic visual impact with low glare lighting performance
- Gimble and rotatable rings gives directional flexibility for both ambient and feature lighting
- Clear tempered glass providing an IP44 protection
- Available in multiple downlights with independent aiming from one fixture
- Ideal for spaces such as retail stores, galleries, foyers, hotels, corridors, function rooms, living areas

TECHNICAL PERFORMANCE


- 2x8W, 2x13W or 2x22W total system power consumption with overload and short circuit protection
- > 65,000 hours lifespan (L70)
- Premium quality Japanese LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K, and 5K colour temperature with low colour shift over time

OPTICAL & THERMAL PERFORMANCE

- Reflector and customised heatsink provides premium optical and thermal performance
- Efficient optical control in various beam angles with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied complete with remote leading and trailing edge mains dimmable driver, which is compatible with a range dimming systems
- All drivers come with quick-connect harness, power cord and plug
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60Hz



ALSO AVAILABLE IN 1 OR 3 LIGHT VERSION

Weight (kg)	3K and 4K	5K								IP44
0.7	CRI >85	CRI >75	108x210	35°	355°					

TOTAL SYSTEM POWER CONSUMPTION = 2x8W / 2x13W / 2x22W

CODE ORDERING GUIDE: PRODUCT CODE /DIMMING SUFFIX (if required) – COLOUR SUFFIX

Example: 1117-SP-3K-8W-01 or 1117-SP-3K-8W/DALI-01

WATT	COLOUR TEMP.					HOT LED LUMENS
		24° SP	36° FL	47° WFL	55° VWFL	
PRODUCT CODES						
2x8W	3K	1057-2L-SP-3K-8W	1057-2L-FL-3K-8W	1057-2L-WFL-3K-8W	-	1656
	4K	1057-2L-SP-4K-8W	1057-2L-FL-4K-8W	1057-2L-WFL-4K-8W	-	1740
	5K	1057-2L-SP-5K-8W	1057-2L-FL-5K-8W	1057-2L-WFL-5K-8W	-	1776
2x13W	3K	1057-2L-SP-3K-13W	1057-2L-FL-3K-13W	-	1057-2L-VWFL-3K-13W	3038
	4K	1057-2L-SP-4K-13W	1057-2L-FL-4K-13W	-	1057-2L-VWFL-4K-13W	3214
	5K	1057-2L-SP-5K-13W	1057-2L-FL-5K-13W	-	1057-2L-VWFL-5K-13W	3292
2x22W	3K	1057-2L-SP-3K-22W	1057-2L-FL-3K-22W	-	1057-2L-VWFL-3K-22W	4828
	4K	1057-2L-SP-4K-22W	1057-2L-FL-4K-22W	-	1057-2L-VWFL-4K-22W	5168
	5K	1057-2L-SP-5K-22W	1057-2L-FL-5K-22W	-	1057-2L-VWFL-5K-22W	5236

DIMMING OPTIONS: ADD SUFFIX AFTER THE CODE

		8W	13W	22W
/DALI	Dali Dimming	✓	✓	✓
/DSI	Digital Dimming	✓	✓	✓
	Switch Dim	✓	✓	✓
/AD	Analogue Dimming 1-10V	✓	✓	✓
	Leading & Trailing edge mains dimming	STANDARD	STANDARD	STANDARD

TRIM COLOUR OPTIONS: ADD SUFFIX AFTER THE CODE

- 01 Satin White
- 06 Matte Black
- 10 Bright Silver