

1117-3L

Riga W3



CONSTRUCTION & DESIGN

- Recessed LED adjustable downlight
- Housing and trim is constructed in steel and finished in satin white powdercoat paint
- Recessed white housing creating a same low glare lighting performance
- Gimble and rotatable rings gives directional flexibility for both ambient and feature lighting
- Clear tempered glass providing an IP44 protection
- Available in multiple downlights with independent aiming from one fixture
- Ideal for spaces such as retail stores, galleries, foyers, hotels, corridors, function rooms, living areas

TECHNICAL PERFORMANCE


- 3x8W, 3x13W or 3x22W total system power consumption with overload and short circuit protection
- > 65,000 hours lifespan (L70)
- Premium quality Japanese LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K, and 5K colour temperature with low colour shift over time

OPTICAL & THERMAL PERFORMANCE

- Reflector and customised heatsink provides premium optical and thermal performance
- Efficient optical control in various beam angles with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied complete with remote leading and trailing edge mains dimmable driver, which is compatible with a range dimming systems
- All drivers come with quick-connect harness, power cord and plug
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60Hz



ALSO AVAILABLE IN 1 OR 2 LIGHT VERSION

Weight (kg)	3K and 4K	5K							IP44
1.0	CRI >85	CRI >75							

TOTAL SYSTEM POWER CONSUMPTION = 3x8W /3x13W /3x22W

CODE ORDERING GUIDE: PRODUCT CODE /DIMMING SUFFIX (if required) – COLOUR SUFFIX

Example: 1117-3L-SP-3K-13W-01 or 1117-3L-SP-3K-13W/DALI-01

WATT	COLOUR TEMP.					HOT LED LUMENS
		24° SP	36° FL	47° WFL	55° VWFL	
PRODUCT CODES						
3x8W	3K	1117-3L-SP-3K-8W	1117-3L-FL-3K-8W	1117-3L-WFL-3K-8W	-	2484
	4K	1117-3L-SP-4K-8W	1117-3L-FL-4K-8W	1117-3L-WFL-4K-8W	-	2610
	5K	1117-3L-SP-5K-8W	1117-3L-FL-5K-8W	1117-3L-WFL-5K-8W	-	2664
3x13W	3K	1117-3L-SP-3K-13W	1117-3L-FL-3K-13W	-	1117-3L-VWFL-3K-13W	4557
	4K	1117-3L-SP-4K-13W	1117-3L-FL-4K-13W	-	1117-3L-VWFL-4K-13W	4821
	5K	1117-3L-SP-5K-13W	1117-3L-FL-5K-13W	-	1117-3L-VWFL-5K-13W	4938
3x22W	3K	1117-3L-SP-3K-22W	1117-3L-FL-3K-22W	-	1117-3L-VWFL-3K-22W	7242
	4K	1117-3L-SP-4K-22W	1117-3L-FL-4K-22W	-	1117-3L-VWFL-4K-22W	7752
	5K	1117-3L-SP-5K-22W	1117-3L-FL-5K-22W	-	1117-3L-VWFL-5K-22W	7854

DIMMING OPTIONS: ADD SUFFIX AFTER THE CODE

		8W	13W	22W
/DALI	Dali Dimming	✓	✓	✓
/DSI	Digital Dimming	✓	✓	✓
	Switch Dim	✓	✓	✓
/AD	Analogue Dimming 1-10V	✓	✓	✓
	Leading & Trailing edge mains dimming	STANDARD	STANDARD	STANDARD

TRIM COLOUR OPTIONS: ADD SUFFIX AFTER THE CODE

-01 Satin White