

1192

Atria



CONSTRUCTION & DESIGN

- Recessed LED fixed downlight with frosted diffuser
- Constructed in die cast aluminium alloy and finished in satin white and matte black powdercoat paint
- Recessed polycarbonate diffuser gives a symmetrical wide beam distribution with high lumen output
- Silicone gasket seal to ceiling providing IP65 protection
- Installation springs suitable for ceiling thickness up to 20mm
- Ideal for spaces such as bathrooms, foyers, hotels, function rooms and general lighting
- Available in medical range

TECHNICAL PERFORMANCE


- 13W or 22W total system power consumption with overload wand short circuit protection
- > 65,000 hours lifespan (L70)
- Premium quality Japanese LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) 2
- Available in 3K, 4K, and 5K colour temperature with low colour shift over time

OPTICAL & THERMAL PERFORMANCE

- Reflector, diffuser and customised heatsink provides premium optical and thermal performance
- Efficient optical control in wide beam angle and no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied complete with remote leading and trailing edge mains dimmable driver, which is compatible with a range dimming systems
- All drivers come with power cord and plug
- Quick connect driver
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60Hz





Weight (kg)	3K and 4K	5 K		\F/		((ID65	
0.3	CRI >85	CRI >75	115		SELV	(6	1265	

TOTAL SYSTEM POWER CONSUMPTION = 13W/22W

CODE ORDERING GUIDE: PRODUCT CODE / DIMMING SUFFIX (if required) - COLOUR SUFFIX Example: 1192-3K-13W-01 or 1192-3K-13W/DALI-01

WATTAGE	COLOUR TEMPERATURE	>55° WIDE	HOT LED LUMENS		
		PRODUCT CODES			
	3K	1192-3K-13W		1519	
13W	4K	1192-4K-13W		1607	
	5K	1192-5K-13W		1646	
	зк	1192-3K-22W	:	2414	
22W	4K	1192-4K-22W	2	2584	
	5K	1192-5K-22W	2	2618	
DIMMING OPTION	ONS: ADD SUFFIX AFTER	R THE CODE	13W 22W		
/DALI D	ali Dimming		✓	√	
/DSI D	igital Dimming		✓	✓	
S	witch Dim		✓	✓	
/AD A	nalogue Dimming 1-10V		✓	✓	
L	Leading & Trailing edge mains dimming			STANDARD	

TRIM COLOUR OPTIONS: ADD SUFFIX AFTER THE CODE

-01 Satin White -06 Matte Black

GAMMA ILLUMINATION