

1210  
1211  
1212

## Sholi

UNIQUE SQUARE  
DOUBLE BATWING  
LIGHT OUTPUT

## CONSTRUCTION &amp; DESIGN

- Recessed LED adjustable downlight
- Trim and housing is constructed in pressure die cast aluminium alloy and finished in satin white, matte black or bright silver powdercoat paint
- Adjustable LED wallwasher has very high lumen output due to the brilliant optical control maintaining an ultra low glare performance
- Ideal applications in shopping centres and retail outlets with advantages of no heat output, less power consumption and long life without maintenance
- Ventilated front housing and tempered safety glass

## TECHNICAL PERFORMANCE

- 28W, 45W or 60W total system power consumption with overload and short circuit protection
- > 65,000 hours lifespan (L70)
- Premium quality Japanese LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K, and 5K colour temperature with low colour shift over time

## OPTICAL &amp; THERMAL PERFORMANCE

- Heatsink manufactured from custom developed aluminium alloy for better and faster heat dissipation
- Efficient optical control with no harsh cut off and ultra low glare
- Unique square double batwing light output

## ELECTRICAL SYSTEM

- Supplied complete with remote non-dimmable driver (refer to dimming options table).
- All drivers come with quick-connect harness, power cord and plug
- Driver is IP64 rated to protect the electronics from humidity and moisture
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60Hz




Easily connects



30W Driver - IP64



45W/60W Driver - IP64



Weight (kg)	3K and 4K	5K							IP44
1.3	CRI >85	CRI >75	220 x130	60°	F	SELV			

TOTAL SYSTEM POWER CONSUMPTION = 28W /45W /60W

CODE ORDERING GUIDE: PRODUCT CODE /DIMMING SUFFIX (if required) – COLOUR SUFFIX  
Example: 1210-3K-01 or 1210-3K/DALI-01

WATTAGE	COLOUR TEMPERATURE	62 x 65° BEAM ANGLE	HOT LED LUMENS
		PRODUCT CODES	
28W	3K	1210-3K	4030
	4K	1210-4K	4264
	5K	1210-5K	4368
45W	3K	1211-3K	6106
	4K	1211-4K	6536
	5K	1211-5K	6620
60W	3K	1212-3K	7247
	4K	1212-4K	7752
	5K	1212-5K	7854

DIMMING OPTIONS: ADD SUFFIX AFTER THE CODE

		28W	45W	60W
/DALI	Dali Dimming	✓	✓	✓
/DSI	Digital Dimming	✓	✓	✓
	Switch Dim	✓	✓	✓
/AD	Analogue Dimming 1-10V	✓		
/DIM	Leading & Trailing edge mains dimming	✓		
	Non-dimmable	STANDARD	STANDARD	STANDARD

TRIM COLOUR OPTIONS: ADD SUFFIX AFTER THE CODE

- 01 Satin White
- 06 Matte Black
- 10 Bright Silver