

1213
1213SM

Cabali



CONSTRUCTION & DESIGN

- Recessed or surface mounted LED fixed downlight
- Constructed in aluminium and finished in satin white, matte black powdercoated paint or brushed aluminium
- Cabali can be surface mounted or recessed as the housing can be removed allowing for the body to be recessed
- Clear tempered glass providing IP44 protection
- Ideal for spaces such as bars, cabinets and display lighting

TECHNICAL PERFORMANCE

- 5W total system power consumption with overload and short circuit protection
- > 65,000 hours lifespan (L70)
- Premium quality Japanese LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K and 4K colour temperature with low colour shift over time


OPTICAL & THERMAL PERFORMANCE

- Reflector and customised heatsink provides premium optical and thermal performance
- Efficient optical control with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied complete with remote leading and trailing edge mains dimmable driver, also compatible with a range of dimming systems
- All drivers come with power cord and plug
- Quick connect driver
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60Hz

RECESSED



SURFACE MOUNT



Weight (kg)	3K and 4K		RECESSED CUT OUT						IP44
0.2	CRI >85								

TOTAL SYSTEM POWER CONSUMPTION = 5W

CODE ORDERING GUIDE: PRODUCT CODE – COLOUR SUFFIX

Example: 1213-3K-5W-01

WATTAGE	COLOUR TEMPERATURE	30° BEAM ANGLE	HOT LED LUMENS
		PRODUCT CODES	
5W	3K	1213-3K	480
	4K	1213-4K	520
5W	3K	1213SM-3K	480
	4K	1213SM-4K	520

SUPPLIED AS STANDARD WITH LEADING & TRAILING EDGE MAINS DIMMABLE DRIVER

TRIM COLOUR OPTIONS: ADD SUFFIX AFTER THE CODE

- 01 Satin White
- 06 Matte Black
- 31 Brushed Aluminium