

1290
1295

Scoop

**CONSTRUCTION & DESIGN**

- Recessed LED adjustable wallwash downlight
- Constructed in pressure die cast aluminium alloy and finished in satin white, matte black or bright silver powdercoat paint
- Adjustable LED downlight provides a 80° tilt angle to ensure good utilisation in commercial and retail environments
- Smooth positive retention and rotation mechanism and featuring passive cooling via a single piece heatsink for LED longevity and high output
- Clear tempered glass providing IP44 protection
- Ideal for shopping centres, retail stores and galleries

TECHNICAL PERFORMANCE

- 22W or 28W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality Japanese LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K, and 5K colour temperature with low colour shift over time

OPTICAL & THERMAL PERFORMANCE


- Reflector and customised heatsink provides premium optical and thermal performance
- Efficient optical control in various beam angles with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied complete with remote driver (refer to dimming options table)
- All drivers come with quick connect harness, power cord and plug
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60Hz



Quick connect



| | | | | | | | | |
|-------------|-----------|---------|------|-----|-----|---|------|------|
| Weight (kg) | 3K and 4K | 5K | | | | | | |
| 0.9 | CRI >85 | CRI >75 | 350° | 80° | 143 | F | SELV | IP44 |

TOTAL SYSTEM POWER CONSUMPTION = 22W / 28W

CODE ORDERING GUIDE: PRODUCT CODE /DIMMING SUFFIX (if required) – COLOUR SUFFIX

Example: 1290-FL-3K-22W-01 or 1290-FL-3K-22W/DALI-01

| WATT | COLOUR TEMP. | | | | HOT LED LUMENS | |
|---|--------------|---------------------------------------|------------|--------------|----------------|----------|
| | | PRODUCT CODES | | | | |
| 22W | 3K | 1290-SP-3K | 1290-FL-3K | 1290-VWFL-3K | 2414 | |
| | 4K | 1290-SP-4K | 1290-FL-4K | 1290-VWFL-4K | 2584 | |
| | 5K | 1290-SP-5K | 1290-FL-5K | 1290-VWFL-5K | 2618 | |
| 28W | 3K | 1295-SP-3K | 1295-FL-3K | 1295-VWFL-3K | 3213 | |
| | 4K | 1295-SP-4K | 1295-FL-4K | 1295-VWFL-4K | 3380 | |
| | 5K | 1295-SP-5K | 1295-FL-5K | 1295-VWFL-5K | 3528 | |
| DIMMING OPTIONS: ADD SUFFIX AFTER THE CODE | | | | | | |
| | /DALI | Dali Dimming | | | 22W | 28W |
| | /DSI | Digital Dimming | | | ✓ | ✓ |
| | | Switch Dim | | | ✓ | ✓ |
| | /AD | Analogue Dimming 1-10V | | | ✓ | ✓ |
| | /DIM | Leading & Trailing edge mains dimming | | | STANDARD | ✓ |
| | | Non-dimmable | | | | STANDARD |

TRIM COLOUR OPTIONS: ADD SUFFIX AFTER THE CODE

- 01 Satin White
- 06 Matte Black
- 10 Bright Silver