

1351

# Syncro-D



IP66

## CONSTRUCTION & DESIGN

- Surface mounted LED wall light
- Constructed from pressure die cast aluminium alloy with extruded aluminium body and finished in textured white, textured black and textured silver durable polyester powdercoated paint
- High performance fixed wall luminaire designed with LED technology providing optimal and uniform light output with low power consumption
- Clear tempered glass lens with silicone seals provide IP66 protection
- Corrosion resistant
- Ideal for indoor and outdoor application where dust or moisture may be present

## TECHNICAL PERFORMANCE

- 13W or 22W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality Japanese LED Module with high lumen output per watt
- Chromaticity tolerance (macAdam step) - 2
- Available in 3K, 4K, and 5K colour temperature with low colour shift over time


## OPTICAL & THERMAL PERFORMANCE

- Customised heatsink provides premium optical and thermal performance
- Efficient optical control with no harsh cut off and ultra low glare

## ELECTRICAL SYSTEM

- Supplied completely assembled with integral leading and trailing edge mains dimmable driver and terminal block
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

261



	ONE WAY	Weight (kg)	3K and 4K	5K				IP66	
		3.8	CRI >85	CRI >75					

TOTAL SYSTEM POWER CONSUMPTION = 13W / 22W

CODE ORDERING GUIDE: PRODUCT CODE / DIMMING SUFFIX (if required) – COLOUR SUFFIX

Example: 1351-VNSP-3K-13W-03 or 1351-VNSP-3K-13W/DALI-03

WATT	COLOUR TEMP.				HOT LED LUMENS
		15° VNSP	24° SP	55° VWFL	
PRODUCT CODES					
13W	3K	1351-VNSP-3K-13W	1351-SP-3K-13W	1351-VWFL-3K-13W	1519
	4K	1351-VNSP-4K-13W	1351-SP-4K-13W	1351-VWFL-4K-13W	1607
	5K	1351-VNSP-5K-13W	1351-SP-5K-13W	1351-VWFL-5K-13W	1646
22W	3K	1351-VNSP-3K-22W	1351-SP-3K-22W	1351-VWFL-3K-22W	2414
	4K	1351-VNSP-4K-22W	1351-SP-4K-22W	1351-VWFL-4K-22W	2584
	5K	1351-VNSP-5K-22W	1351-SP-5K-22W	1351-VWFL-5K-22W	2618
DIMMING OPTIONS: ADD SUFFIX AFTER THE CODE				13W	22W
/DALI	Dali Dimming			✓	✓
/DSI	DSI Dimming			✓	✓
	Switch Dim			✓	✓
/AD	Analogue Dimming 1-10V			✓	✓
	Leading & Trailing edge mains dimming			STANDARD	STANDARD

COLOUR OPTIONS: ADD SUFFIX AFTER THE CODE

- 03 Textured White
- 07 Textured Black
- 11 Textured Silver