

1358





CONSTRUCTION & DESIGN

- LED exterior luminaire for wall or ceiling application
- Constructed in pressure die cast aluminium alloy and finished in textured white, textured black and textured silver durable powdercoat paint
- Impact resistant opal polycarbonate diffuser providing uniform low glare illumination
- Silicone gaskets and stainless steel fasteners provide IP65 weather protection
- 20mm cable entry
- Ideal for facades, walkways and perimeter lighting for residential and commercial buildings with low maintenance

TECHNICAL PERFORMANCE


- 13W or 22W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality Japanese LED Module with high lumen output per watt
- Chromaticity tolerance (macAdam step) 2
- Available in 3K, 4K, and 5K colour temperature with low colour shift over time

OPTICAL & THERMAL PERFORMANCE

- Components are mounted on die cast aluminium housing for optimal heat sinking
- LED thermal management incorporates both conduction and natural convention to transfer heat rapidly away from LED source to achieve maximum life of LED
- High efficiency white reflector for brilliant optical control with no harsh cut off and polycarbonate diffuser to provide low glare illumination

ELECTRICAL SYSTEM

- Supplied completely assembled with integral leading and trailing edge dimmable driver and terminal block
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz



Weight (kg)	3K and 4K	5K	\	Ш	"	IP65 🔊 🔊
1.6	CRI >85	CRI >75	V	三	6	11-02

TOTAL SYSTEM POWER CONSUMPTION = 13W / 22W

CODE ORDERING GUIDE: PRODUCT CODE - COLOUR SUFFIX

Example: 1358-3K-13W-03

WATTAGE	COLOUR TEMPERATURE	>55° WIDE	HOT LED LUMENS			
		PRODUCT CODES				
	3K	1358-3K-13W	1519			
13W	4K	1358-4K-13W	1607			
	5K	1358-5K-13W	1646			
	3K	1358-3K-22W	2414			
22W	4K	1358-4K-22W	2584			
	5K	1358-5K-22W	2618			

supplied as standard with integral leading & trailing edge mains dimmable driver

TRIM COLOUR OPTIONS: ADD SUFFIX AFTER THE CODE

-03 Textured White

Textured Black

-11 Textured Silver

GAMMA ILLUMINATION