




Wall Lights | 220-240 V | 1x2G11
1043



Technical data	
Collection	linealight
Installation position	Wall lights
Installation environment	Indoor
Power	1 x 55 W
Lamp cap	1 x 2G11
Frequency	50 - 40 Hz
Optic	Diffused
Light emission direction	frontal
Safety class	1
IP	IP20
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	Yes
Emergency mode	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing casing	
Material	Iron
Colour	nickel
Processing	Electroplating

Finishing diffuser	
Material	Glass - Glass
Colour	white - white
Processing	Sandblasting - Silk-screening

Finishing mounting frame	
Material	Iron
Colour	white
Processing	Coating

Wall Lights | 220-240 V | 1x2G11
1043

Double emission wall lights for indoor application. Fluorescent lamp included 55W, lamp cap 1x2G11.

The device body is made of iron and features a nickel finish, processed by means of electroplating; the diffuser is made of glass with a sandblasting treatment; the diffuser is made of glass with a silk-screening treatment; the mounting frame is made of iron, with a white finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 3.260 kg. The power supply driver is included in the delivery.

The device features protection class I and can be wall lights-mounted.

Illuminotechnical Features	
Light Output Ratio (LOR)	100 %
Luminous flux (source)	4800 lm
Luminaire luminous flux	4800 lm
Consumption	59 W
Luminaire efficacy	81 lm/W
Colour temperature	3000 K
Colour rendering index	89 Ra

UGR	
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20
UGR transversal	< 25
UGR axial	< 19

