



Wall Lights | 220-240 V | 1xG5
3695



Technical data	
Collection	linealight
Installation position	Wall lights
Installation environment	Indoor
Power	1 x 24 W
Lamp cap	1 x G5
Frequency	50 - 60 Hz
Optic	Diffused
Light emission direction	downward
Safety class	1
IP	IP20
Glow wire test	No°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	Yes
Emergency mode	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing casing	
Material	Iron
Colour	grey RAL 9006
Processing	Coating

Finishing diffuser	
Material	PMMA
Colour	white
Processing	Satin finishing

Finishing mounting frame	
Material	Iron
Colour	grey RAL 9006
Processing	Coating



Wall Lights | 220-240 V | 1xG5
3695

Single emission wall lights for indoor application. Fluorescent lamp included 24W, lamp cap 1xG5.

The device body is made of iron and features a grey ral 9006 finish, processed by means of coating; the diffuser is made of pmma with a satin finishing treatment; the mounting frame is made of iron, with a grey ral 9006 finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 1.570 kg. The power supply driver is included in the delivery.

The device features protection class I and can be wall lights-mounted.

Illuminotechnical Features

Luminous flux (source)	2000 lm
Colour temperature	3000 K
Colour rendering index	80 Ra