




Wall Lights | 220-240 V | topLED 14 W 350 mA | CRI 83
7908



Technical data	
Collection	linealight
Installation position	Wall lights
Installation environment	Indoor
Light Source	LED
Circuit structure	topLED
Optic	Diffused
Light emission direction	downward
Power	14 W
Luminous flux (source)	1449 lm
Frequency	50 - 60 Hz
CCT / Tonalità	3000 K
Colour rendering index	83 Ra
AC / DC	AC
Safety class	1
IP	IP44
Glow wire test	650°
Operating temperature	70 °C
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	Yes
Induzione	No
Emergency mode	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing casing	
Material	Aluminium
Colour	embossed white RAL 9003
Processing	Coating

Finishing diffuser	
Material	PMMA
Colour	white
Processing	Silk-screening

Finishing mounting frame	
Material	Iron
Colour	white
Processing	Coating

Wall Lights | 220-240 V | topLED 14 W 350 mA | CRI 83
7908

Double emission wall lights for indoor application. The warm white LED light source with a diffused light distribution is composed of 36 topLED LEDs with CCT of 3000 K and a CRI 83; the source luminous flux is 1449 lm, with a 103.5 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The device body is made of aluminium and features a embossed white ral 9003 finish, processed by means of coating; the diffuser is made of pmma with a silk-screening treatment; the mounting frame is made of iron, with a white finish, processed by means of coating. The ingress protection degree is IP44; the total weight is of 0.960 kg. The power supply driver is included in the delivery.

The total absorbed power is 14 W.

The device features protection class I and can be wall lights-mounted.

Illuminotechnical Features	
Light Output Ratio (LOR)	65 %
Luminous flux (source)	1449 lm
Luminaire luminous flux	956 lm
Consumption	14 W
Luminaire efficacy	69 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	83 Ra

UGR	
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20
UGR transversal	< 19
UGR axial	< 25

