


Halfpipe



Wall Lights | 220-240 V | topLED 12 W 350 mA | CRI 90
8396



Technical data	
Installation position	Wall lights
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward
Power	12 W
Luminous flux (source)	1511 lm
Frequency	60 - 50 Hz
CCT / Tonaltà	3000 K
Colour rendering index	90 Ra
Safety class	1
IP	IP44
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	Yes
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	Yes
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing diffuser	
Colour	opaline

Finishing mounting frame	
Material	Aluminium
Colour	translucent



Wall Lights | 220-240 V | topLED 12 W 350 mA | CRI 90
8396

Single emission wall lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 30 topped LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 1511 lm, with a 125.9 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

; the mounting frame is made of aluminium, with a translucent finish. The ingress protection degree is IP44; The power supply driver is included in the delivery.

The total absorbed power is 12 W.

The device features protection class I and can be wall lights-mounted.

Illuminotechnical Features

Luminous flux (source)	1511 lm
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Life / Failure ratio	L80C0B20