




Downlights | 1 x powerLED 1,5 W 500 mA | CRI 80
86408W30









Technical data	
Installation position	Wall lights - Ceiling
Installation environment	Indoor
Light Source	LED
Optic	30°
Power	1.5 W
Luminous flux (source)	178 lm
Current intensity	500mA
CCT / Tonaltà	3000 K
Colour rendering index	80 Ra
C.C. / C.V.	CC
Safety class	3
IP	IP44
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Operating temperature	-20°C / +50°C
Driver included	No
Induzione	No
Emergency mode	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	0.12 m
Resin potting	Yes

Finishing casing

Material	Brass
Colour	chrome
Processing	Electroplating

Electronics

	On/Off Driver 1 art.
	On/Off Driver 2 art.
	On/Off Driver 3 art.
	On/Off Driver 6 art.
	DALI - Push and Simply Dim 1 art.
	1-10V - N/O button 1 art.

Downlights | 1 x powerLED 1,5 W 500 mA | CRI 80
86408W30

Single emission downlights for indoor application. The warm white LED light source with a 30° light distribution is composed of 1 powered LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 178 lm, with a 178.0 lm/W nominal luminous efficacy.



The device body is made of brass and features a chrome finish, processed by means of electroplating. The ingress protection degree is IP44; the total weight is of 0.080 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 1,5 W. The power supply cable is included and features.

The device features protection class III and can be wall lights or ceiling-mounted with an outer casing, code 84956(for concrete or masonry).

Illuminotechnical Features	
Light Output Ratio (LOR)	86 %
Luminous flux (source)	178 lm
Luminaire luminous flux	154 lm
Consumption	1,5 W
Luminaire efficacy	102 lm/W
Colour temperature	3000 K
Colour rendering index	80 Ra

UGR	
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20
UGR transversal	> 25
UGR axial	> 25





Outer casing
L=69mm, H=60mm, D=60mm

Code
84901



Outer casing
L=73mm, H=60mm, D=60mm

Code
84956