




Downlights | arrayLED 13 W 350 mA | CRI 92 | Warm Tune  
**91785S60**



95



Technical data	
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Optic	60°
Power	13 W
Luminous flux (source)	1000 lm
Current intensity	350mA
CCT / Tonalità	Warm Tune
Colour rendering index	92 Ra
C.C. / C.V.	CC
Safety class	3
IP	IP44
IK	05
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	No
Induzione	No
Emergency mode	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	0.30 m
Resin potting	No

Finishing casing	
Material	steel
Colour	embossed white RAL 9003
Processing	Coating



Downlights | arrayLED 13 W 350 mA | CRI 92 | Warm Tune  
**91785S60**

Single emission downlights for indoor application. The warm tune LED light source with a 60° light distribution is composed of 1 arrayled LEDs with CCT of 1800K-3000K K and a CRI 92; the source luminous flux is 1000 lm, with a 76.9 lm/W nominal luminous efficacy.

The device body is made of steel and features a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP44; the total weight is of 0.511 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 13 W. The power supply cable is included and features.

The device features protection class III and can be ceiling-mounted, with a 95 mm diameter hole (in plasterboard).

#### **Illuminotechnical Features**

Luminous flux (source)	1000 lm
Colour rendering index	92 Ra