



Sugar Surfaced

Nahrang Design


00-5297-14-23

Pendant Sugar Surfaced LED 26.6W 2700K White Gold 1575lm



TECHNICAL FEATURES

IP20



Power (W) : 26.6W

Total power consumption of light (W) : 28.5W

Real lumens : 1575

Real lm/W : 55

Correlated Colour Temperature (CCT) : LED warm-white 2700K

Lens / reflector angle : HORIZONTAL 115°

UGR : <=22

Structure material : Aluminium

Structure finish : White, Gold

Diffuser material : Acrylic

Diffuser finish : Opal

Equipment included : Yes, electronic

Voltage / frequency : 100-240V/50-60Hz

Warranty : 5 Years

Useful life : 50.000h L80B20

Max. temperature : 25°C

Energy efficiency : LED A++

LUMINOTECHNIC FEATURES

Light source: LED CREE

CRI: 80

MacAdam steps: 2


Photobiological risk: RG1

UGR

UGR crosswise: 21.9

UGR lengthwise: 21.8

UGR	
S=0.250	
Ceiling / cavity	0.7
Walls	0.5
Working Plane	0.2
Room dimensions	X=4H, Y=8H
UGR crosswise	21.9
UGR lengthwise	21.8



LOGISTICS

Net weight (kg): 2.54

Packaged weight (kg): 4.28

Packaging: 455mm x 450mm x 295mm



