
Wall Lights | 220-240 V 35 topLED 14 W DC - 17 W AC | CRI 90 8185

## 



EIIE 🔤 CE 💉 🕱 🗘 🛓 C.C. 🦳 1940 🗌

Technical data		
Designer	Pio e Tito Toso	
Construction year	2016	
Туре	Surface	
Installation position	Wall lights	
Installation environment	Indoor	
Light Source	LED	
Optics	General Lighting	
Light emission direction	downward and upward	
Power	14 W	
Source lumens	2021 lm	
Frequency	60 - 50 Hz	
CCT / Tone	3000 K	
Colour rendering index	90 Ra	
C.C. / C.V.	AC	
Safety class	1	
IP	IP40	
Glow wire test	650°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
Driver included	Driver	
Dimmable article	DALI	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	No	
Resin potting	No	
Type of light emission	Double emission	
Net weight	1.326 Kg	
Electrostatic discharge protection	No	
Surge protection	No	

Finishing casing		
Material	PU	
Colour	white	
Finishing diffus	er	
Material	PMMA	
Colour	transparent	
Processing	Laser engravings	

13.07.2021

## Oxygen\_W1

## Wall Lights | 220-240 V | 35 topLED 14 W DC - 17 W AC | CRI 90 | Base 8185

Double emission wall lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 35 topled LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 2021 lm, with a 144.4 lm/W nominal luminous efficacy.


The device body is made of pu and features a white finish; the diffuser is made of pmma with a laser engravings treatment. The ingress protection degree is IP40; the total weight is of 1.326 kg.

The total absorbed power is 14 W.

The device features protection class I and can be wall lights-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features	
Light Output Ratio (LOR)	39 %
Source lumens	2021 lm
Delivered lumens	789 lm
Consumption	17 W
Luminaire efficacy	46 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25
LED Life / Failure Ratio	
L80 B20 C0 80000h	



Oxygen\_W1 | Wall Lights | Accessories 8185





Dimmer Bluetooth, 220-240V Code KIT0079