



Wall Lights | 220-240 V 35 topLED 14 W DC - 17 W AC | CRI 90 8496







Technical data			
Construction year	2018		
Туре	Surface		
Installation position	Wall lights		
Installation environment	Indoor		
Light Source	LED		
Optics	General Lighting		
Light emission direction	downward and upward		
Power	14 W		
Source lumens	2021 lm		
Frequency	60 - 50 Hz		
CCT / Tone	3000 K		
Colour rendering index	90 Ra		
C.C. / C.V.	AC		
Safety class	1		
IP	IP40		
Glow wire test	650°		
Direct mounting on normally flammable surfaces	Yes		
CE	Yes		
Driver included	Driver		
Dimmable article	Phase cut		
Directional	No		
Tilting	No		
Walk-over	No		
Drive-over	No		
Cable included	No		
Resin potting	No		
Type of light emission	Double emission		
Net weight	1.270 Kg		
Electrostatic discharge protection	No		
Surge protection	No		

Finishing casing	
Material	PU
Colour	white
Finishing diffuser	
Material	PMMA
Colour	transparent
Processing	Laser engravings

## Oxygen\_W1



Wall Lights | 220-240 V | 35 topLED 14 W DC - 17 W AC | CRI 90 | Base  $\bf 8496$ 

Double emission wall lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 35 topled LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 2021 lm, with a 144.4 lm/W nominal luminous efficacy.

The device body is made of pu and features a white finish; the diffuser is made of pmma with a laser engravings treatment. The ingress protection degree is IP40; the total weight is of 1.270 kg.

The total absorbed power is 14 W.

The device features protection class I and can be wall lights-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features				
Light Output Ratio (LOR)	39 %			
Source lumens	2021 lm			
Delivered lumens	789 lm			
Consumption	17 W			
Luminaire efficacy	46 lm/W			
Colour temperature	3000 K			
Standard Deviation of Colour Matching	3 Step MacAdam			
Colour rendering index	90 Ra			
Junction temperature (lighting fixture)	80			
Standard Operating Ambient Temperature	25			
LED Life / Failure Ratio				
L80 B20 C0 80000h				

135°	150°	165°	180° 150	165°	150°	135°
120°	X		90		X	120°
105°	1		60		1	105°
90°			>			90°
75°					X	75°
60°						60°
45°	30°	15°	0°	15°	30°	45°
cd/klm — C0/C180 — C90/C270						η = 100%

## Oxygen\_W1



Oxygen\_W1 | Wall Lights | Accessories **8496** 





Dimmer 220-240V Code KIT0026



Dimmer
Radio-frequenza, 85-240V

Code KIT0080