Floor Lamp | 220-240 V | 1xE27 12102



| Technical data | |
|--|------------------|
| Туре | Floor Lamp |
| Installation position | Floor |
| Installation environment | Indoor |
| Lamp cap | 1 x E27 Max 46W |
| Frequency | 50-60 Hz |
| Optics | General Lighting |
| Light emission direction | upward |
| Safety class | 2 |
| IP | IP20 |
| Glow wire test | 650° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| Dimmable article | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | Yes |
| Cable length | 2 m |
| Electric socket | Туре С |
| Resin potting | No |
| Net weight | 1.675 Kg |



| Finishing diffuser | | | |
|-----------------------------------|--------------|--|--|
| Material | PE | | |
| Colour | neutral | | |
| | | | |
| | | | |
| Finishing mou | inting frame | | |
| Finishing mo u Material | Inting frame | | |

Floor Lamp | 220-240 V | 1xE27 12102

Single emission floor lamp for indoor application. Compatibility: LED lamp, halogen 46 W, compact fluo 20 W; lamp cap 1xE27.

The diffuser is made of pe; the mounting frame is made of PC, with a white finish. The ingress protection degree is IP20; the total weight is of 1.675 kg.

. The power supply cable is included and features a 2 m lenght.

The device features protection class II and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

| Illuminotechnical Features | |
|---|--------|
| Source lumens | 700 lm |
| Colour rendering index | 100 Ra |
| Junction temperature (lighting fixture) | 80 |
| Standard Operating Ambient Temperature | 25 |