## Oh!\_S LED

Ceiling Lights | 220-240 V 1 topLED 8 W DC - 8 W AC | CRI 80 12131

EAC	CE	ROHS	$\overline{\mathbb{X}}$	٢	C.C.	IP20	_

 $\bigcirc$ 



Technical data			
Туре	Surface		
Installation position	Ceiling		
Installation environment	Indoor		
Light Source	LED		
Optics	General Lighting		
Light emission direction	downward		
Power	8 W		
Source lumens	1002 lm		
Frequency	60 - 50 Hz		
CCT / Tone	3000 K		
Colour rendering index	80 Ra		
C.C. / C.V.	AC		
Safety class	2		
IP	IP20		
Glow wire test	850°		
Direct mounting on normally flammable surfaces	Yes		
CE	Yes		
Driver included	Driver		
Dimmable article	No		
Directional	No		
Tilting	No		
Walk-over	No		
Drive-over	No		
Cable included	No		
Resin potting	No		
Type of light emission	Single emission		
Net weight	0.948 Kg		
Electrostatic discharge protection	No		
Surge protection	No		

Finishing diff		
Material	PE	
Colour	neutral	
Finishing mou	unting frame	
Material	PC	

## Oh!\_S LED

## Ceiling Lights | 220-240 V | 1 topLED 8 W DC - 8 W AC | CRI 80 | Base 12131

Single emission ceiling lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 1 topled LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 1002 lm, with a 125.3 lm/W nominal luminous efficacy.

The diffuser is made of pe; the mounting frame is made of PC, with a white finish. The ingress protection degree is IP20; the total weight is of 0.948 kg.

The total absorbed power is 8 W.

The device features protection class II and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features			
Light Output Ratio (LOR)	84 %		
Source lumens	1002 lm		
Delivered lumens	845 lm		
Consumption	8 W		
Luminaire efficacy	105 lm/W		
Colour temperature	3000 K		
Standard Deviation of Colour Matching	3 Step MacAdam		
Colour rendering index	80 Ra		
Junction temperature (lighting fixture)	80		
Standard Operating Ambient Temperature	25		
UGR			
UGR transversal	17.2		
UGR axial	15.1		
X=4H   Y=8H	S=0.25H		
Reflection factor	70/50/20		
OPTICAL			
Light distribution simmetry	Symmetrical		
C0/C180 optics	180°		

