




Submerged | 220-240 V | 1 x powerLEDs 0,5 W 230 V  
 RGB  
**15158**



Technical data	
Type	Submerged
Installation position	Floor
Installation environment	Outdoor
Light Source	LED
Circuit structure	powerLEDs
Optics	General Lighting
Power	0.5 W
Frequency	60 - 50 Hz
CCT / Tone	RGB
AC / DC	AC
Safety class	2
IP	IP68
IK	IK10
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Fire Rated (BS 476 PT21 compliant)	No
Driver included	Driver
Min duration	12 h
Max duration	14.5 h
Charging time	6 h
Emergency mode	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Single emission
Net weight	1.180 Kg

Finishing diffuser	
Material	PE
Colour	neutral

Finishing mounting frame	
Material	PE
Colour	white



Submerged | 220-240 V | 1 x powerLEDs 0,5 W 230 V | RGB  
**15158**

Single emission floor lamp for outdoor application. The RGB LED light source with a general lighting light distribution is composed of 1.

The diffuser is made of pe; the mounting frame is made of pe, with a white finish. The ingress protection degree is IP68; the total weight is of 1.180 kg.

The total absorbed power is 0,5 W.

The device features protection class II and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features	
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25