

Ceiling Lights | 1 topLED 8 W DC 350 mA | CRI 80 **16112**







Technical data		
Туре	Surface	
Installation position	Wall lights - Ceiling	
Installation environment	Outdoor	
Light Source	LED	
Optics	General Lighting	
Light emission direction	downward	
Power	8 W	
Source lumens	1002 lm	
Current intensity	350mA	
CCT / Tone	3000 K	
Colour rendering index	80 Ra	
C.C. / C.V.	CC	
Safety class	3	
IP	IP65	
IK	IK10	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
Driver included	No	
Dimmable article	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	No	
Resin potting	No	
Type of light emission	Single emission	
Net weight	0.948 Kg	
Electrostatic discharge protection	No	
Surge protection	No	

Finishing diffuser			
Material	PE		
Colour	neutral		
Finishing mounting frame			
Material	PC		
Colour	white		

Oh!_S65 LED



Ceiling Lights | 1 topLED 8 W DC 350 mA | CRI 80 **16112**

Single emission ceiling lights for outdoor application. The warm white LED light source with a general lighting light distribution is composed of 1 topled LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 1002 lm, with a 125.3 lm/W nominal luminous efficacy.

The diffuser is made of pe; the mounting frame is made of PC, with a white finish. The ingress protection degree is IP65; the total weight is of 0.948 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 8 W.

The device features protection class III and can be wall lights or ceilingmounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features	
Source lumens	1002 lm
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	80 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25

Oh!_S65 LED



Oh!_S65 LED | Ceiling Lights | Accessories **16112**





Power supply

Code KIT0066