


Oh!_P65 E27



Pendant Luminaires | 220-240 V | 1xE27
16168



| Technical data | |
|--|------------------|
| Type | Surface |
| Installation position | Ceiling |
| Installation environment | Outdoor |
| Lamp cap | 1 x E27 Max 46W |
| Frequency | 50-60 Hz |
| Optics | General Lighting |
| Light emission direction | downward |
| Safety class | 2 |
| IP | IP65 |
| IK | IK10 |
| Glow wire test | 650° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| Dimmable article | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | Yes |
| Cable length | 2.8 m |
| Resin potting | No |
| Net weight | 2.200 Kg |

| Finishing casing | |
|------------------|-------|
| Material | PE |
| Colour | white |

| Finishing diffuser | |
|--------------------|---------|
| Material | PE |
| Colour | neutral |

| Finishing mounting frame | |
|--------------------------|---------|
| Material | Iron |
| Processing | Coating |

| Cables Pendant Luminaires | |
|---------------------------|---------|
| Max cable length | 2800 mm |



Pendant Luminaires | 220-240 V | 1xE27
16168

Double emission pendant luminaires for outdoor application.

Compatibility: LED lamp, compact fluo 20 W, halogen 46 W; lamp cap 1xE27.

The device body is made of pe and features a white finish; the diffuser is made of pe; the mounting frame is made of iron, processed by means of coating. The ingress protection degree is IP65; the total weight is of 2.200 kg.

. The power supply cable is included and features a 2.8 m lenght.

The device features protection class II and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features

| | |
|---|--------|
| Source lumens | 700 lm |
| Colour rendering index | 100 Ra |
| Junction temperature (lighting fixture) | 80 |
| Standard Operating Ambient Temperature | 25 |