


Oh!_FL65 LED



Floor Lamp | 220-240 V | 1 topLED 15 W DC 350 mA
CRI 90
16191



Technical data	
Type	Floor Lamp
Installation position	Floor
Installation environment	Outdoor
Light Source	LED
Optics	General Lighting
Light emission direction	upward
Power	15 W
Source lumens	1893 lm
Frequency	60 - 50 Hz
CCT / Tone	3000 K
Colour rendering index	90 Ra
C.C. / C.V.	AC
Safety class	2
IP	IP65
IK	IK10
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	5 m
Electric socket	Type F
Resin potting	No
Type of light emission	Double emission
Net weight	2.600 Kg
Electrostatic discharge protection	No
Surge protection	No

Finishing diffuser	
Material	PE
Colour	neutral

Finishing mounting frame	
Material	PC
Colour	white



Floor Lamp | 220-240 V | 1 topLED 15 W DC 350 mA | CRI 90
16191

Double emission floor lamp for outdoor application. The warm white LED light source with a general lighting light distribution is composed of 1 topped LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 1893 lm, with a 126.2 lm/W nominal luminous efficacy.

The diffuser is made of pe; the mounting frame is made of PC, with a white finish. The ingress protection degree is IP65; the total weight is of 2.600 kg.

The total absorbed power is 15 W. The power supply cable is included and features a 5 m lenght.

The device features protection class II and can be floor-mounted with an outer casing, code 14930(for concrete or masonry).


Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features

Source lumens	1893 lm
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25




16191




Outer casing - outer casing for installation on ground or on concrete

Code
14930




Pegs
installation position: land,Cover material: pc

Code
14931



anti-theft - anti-theft ground fixing bracket

Code
14080



Tie rods

Code
53890



Connector

Code
14992