
Oh! Smash_FL65



Floor Lamp | 220-240 V | 1xE27 16215







T I I I. I		
Technical data		
Туре	Floor Lamp	
Installation position	Floor	
Installation environment	Outdoor	
Lamp cap	1 x E27 Max 30W	
Frequency	50-60 Hz	
Optics	General Lighting	
Light emission direction	downward	
Safety class	2	
IP	IP65	
IK	IK10	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
Dimmable article	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	Yes	
Cable length	5 m	
Electric socket	Type F	
Resin potting	No	
Net weight	2.040 Kg	

Finishing diffuser					
Material	PE				
Colour	translucent	translucent			
Finishing mounting frame					
Material	PC				
Colour	white				

Oh! Smash_FL65



Floor Lamp | 220-240 V | 1xE27 16215

Single emission floor lamp for outdoor application. Compatibility: LED lamp, halogen 30 W, compact fluo 14 W; lamp cap 1xE27.

The diffuser is made of pe; the mounting frame is made of PC, with a white finish. The ingress protection degree is IP65; the total weight is of 2.040 kg.

. The power supply cable is included and features a 5 m lenght.

The device features protection class II and can be floor-mounted with an outer casing, code 14930(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features			
Source lumens	405 lm		
Colour rendering index	100 Ra		
Junction temperature (lighting fixture)	80		
Standard Operating Ambient Temperature	25		

Oh! Smash_FL65



Oh! Smash_FL65 | Floor Lamp | Accessories **16215**

H.	22	Outer casing - outer casing for installation on ground or on concrete	Code 14930
111	30 S	Pegs installation position: land,Cover material: pc	Code 14931