Oh! Dynamic White



Floor Lamp | 1 x powerLED 4 W DC 220 mA | CRI 80 Dynamic White 16227





Technical data		
Туре	Floor Lamp	
Installation position	Floor - Land	
Installation environment	Outdoor	
Light Source	LED	
Optics	General Lighting	
Light emission direction	downward and upward	
Power	4 W	
Current intensity	220mA	
CCT / Tone	Dynamic White	
Colour rendering index	80 Ra	
C.C. / C.V.	CC	
Safety class	3	
IP	IP65	
Glow wire test	650°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
Driver included	No	
Dimmable article	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	Yes	
Cable length	5 m	
Resin potting	No	
Type of light emission	Double emission	
Net weight	1.440 Kg	
Electrostatic discharge protection	No	
Surge protection	No	

Finishing casing				
Material	PC			
Colour	white	white		
Finishing diffu	ser			
Material	PE			
Colour	neutral			
Electronics				



Switching Driver 88~264V AC / 125~373V DC 75 W

Oh! Dynamic White



Floor Lamp | 1 x powerLED 4 W DC 220 mA | CRI 80 | Dynamic White $\bf 16227$

Double emission floor lamp for outdoor application. The dynamic white LED light source with a general lighting light distribution is composed of 1 topled LEDs with CCT of 1800K-5000 K and a CRI 80.

The device body is made of PC and features a white finish; the diffuser is made of pe. The ingress protection degree is IP65; the total weight is of 1.440 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 4 W. The power supply cable is included and features a 5 m lenght.

The device features protection class III and can be floor or land-mounted with an outer casing, code 14930(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features	
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	80 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25
LED Life / Failure Ratio	
L70 B20 C0 50000h (at Tj 115 Ta 25)	

Oh! Dynamic White



Oh! Dynamic White | Floor Lamp | Accessories 16227

J.	22	Outer casing - outer casing for installation on ground or on concrete	Code 14930
1111	30 Ø 13	Pegs installation position: land,Cover material: pc	Code 14931
		Connector	Code 14992
	-53.00 mm - 17.50 mm	Remote RF - Dynamic white controller	Code 99701