


Oh! Dynamic White



Floor Lamp | 1 x powerLED 13 W DC 220 mA | CRI 80
Dynamic White
16229



| Technical data | |
|--|---------------------|
| Type | Floor Lamp |
| Installation position | Floor - Land |
| Installation environment | Outdoor |
| Light Source | LED |
| Optics | General Lighting |
| Light emission direction | downward and upward |
| Power | 13 W |
| Current intensity | 220mA |
| CCT / Tone | Dynamic White |
| Colour rendering index | 80 Ra |
| C.C. / C.V. | CC |
| Safety class | 3 |
| IP | IP65 |
| Glow wire test | 650° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| Driver included | No |
| Dimmable article | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | Yes |
| Cable length | 5 m |
| Resin potting | No |
| Type of light emission | Double emission |
| Net weight | 4.7 Kg |
| Electrostatic discharge protection | No |
| Surge protection | No |

| Finishing casing | |
|------------------|-------|
| Material | PC |
| Colour | white |

| Finishing diffuser | |
|--------------------|---------|
| Material | PE |
| Colour | neutral |

Electronics



99741
Multi Channel 24~48V DC



84647
Switching Driver 88~264V AC / 125~373V DC 75 W



Floor Lamp | 1 x powerLED 13 W DC 220 mA | CRI 80 | Dynamic White
16229

Double emission floor lamp for outdoor application. The dynamic white LED light source with a general lighting light distribution is composed of 1 topped LEDs with CCT of 1800K-5000 K and a CRI 80.

The device body is made of PC and features a white finish; the diffuser is made of pe. The ingress protection degree is IP65; the total weight is of 4.7 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 13 W. The power supply cable is included and features a 5 m lenght.

The device features protection class III and can be floor or land-mounted with an outer casing, code 14930(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features

| | |
|---|----------------|
| Standard Deviation of Colour Matching | 3 Step MacAdam |
| Colour rendering index | 80 Ra |
| Junction temperature (lighting fixture) | 80 |
| Standard Operating Ambient Temperature | 25 |

LED Life / Failure Ratio

L70 B20 C0 50000h (at Tj 115 Ta 25)




Oh! Dynamic White | Floor Lamp | Accessories
16229



Outer casing - outer casing for installation on ground or on concrete

Code
14930



anti-theft - anti-theft ground fixing bracket

Code
14081



Connector

Code
14992



Remote RF - Dynamic white controller

Code
99701