




Pendant Luminaires | 30 topLED 9 W DC 50 mA
CRI 90
7948



Technical data	
Type	Surface
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward and upward
Power	9 W
Source lumens	870 lm
Frequency	50-60 Hz
CCT / Tone	3000 K
Colour rendering index	90 Ra
C.C. / C.V.	AC
Safety class	1
IP	IP20
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Dimmable article	Yes
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	2.3 m
Resin potting	No
Type of light emission	Double emission
Net weight	1.198 Kg
Electrostatic discharge protection	No
Surge protection	No

Finishing casing	
Material	Aluminium
Colour	white
Processing	Coating

Finishing diffuser	
Material	PE
Colour	neutral

Finishing mounting frame	
Material	Aluminium
Colour	white
Processing	Coating

Pendant Luminaires | 30 topLED 9 W DC 50 mA | CRI 90 | Base 7948


Double emission pendant luminaires for indoor application. The warm white LED light source with a general lighting light distribution is composed of 30 topLEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 870 lm, with a 96.7 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a white finish, processed by means of coating; the diffuser is made of pe; the mounting frame is made of aluminium, with a white finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 1.198 kg.

The total absorbed power is 9 W. The power supply cable is included and features a 2.3 m length.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.



Distance [m]	Cone diameter [m]	illuminance [lx]
0.5	1.44 1.51	E(0°) 791 E(C90) 76 E(C0) 69
1.0	2.88 3.02	E(0°) 198 E(C90) 19 E(C0) 17
1.5	4.32 4.53	E(0°) 88 E(C90) 8 E(C0) 8
2.0	5.76 6.04	E(0°) 49 E(C90) 5 E(C0) 4
2.5	7.19 7.55	E(0°) 32 E(C90) 3 E(C0) 3
3.0	8.63 9.07	E(0°) 22 E(C90) 2 E(C0) 2

— C0/C180 (Half-peak divergence: 113.0°)
— C90/C270 (Half-peak divergence: 110.4°)

Illuminotechnical Features

Light Output Ratio (LOR)	95 %
Source lumens	870 lm
Delivered lumens	830 lm
Consumption	9 W
Luminaire efficacy	92 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25

LED Life / Failure Ratio

L80 B20 C0 80h	
----------------	--

UGR

UGR axial	16.2
UGR transversal	16.6
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

Light distribution simmetry	Symmetrical
C0/C180 optics	110°



Dimmer
220-240V

Code
KIT0026