





Floor Lamp | 220-240 V | topLED 36 W 900 mA  
CRI 90  
**8910**



Technical data	
Construction year	2019
Type	Floor Lamp
Installation position	Floor
Installation environment	Indoor
Light Source	LED
Circuit structure	topLED
Optics	General Lighting
Light emission direction	upward
Power	36 W
Source lumens	3847 lm
Frequency	60 - 50 Hz
CCT / Tone	3000 K
Colour rendering index	90 Ra
AC / DC	AC
Safety class	1
IP	IP20
Optical compartment IP	IP40
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Fire Rated (BS 476 PT21 compliant)	No
Driver included	Driver
Dimmable article	PUSH DIM
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	4000 m
Electric socket	Type C
Resin potting	No
Type of light emission	Single emission
Electrostatic discharge protection	No
Surge protection	No

Finishing casing	
Material	PC
Colour	transparent
Processing	Sandblasting

Finishing diffuser	
Material	PMMA
Colour	transparent
Processing	Silk-screening

Finishing base	
Material	Iron
Colour	embossed white RAL 9003



Floor Lamp | 220-240 V | topLED 36 W 900 mA | CRI 90  
**8910**

Single emission floor lamp for indoor application. The warm white LED light source with a general lighting light distribution is composed of 1 topped LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 3847 lm, with a 106.9 lm/W nominal luminous efficacy.

The device body is made of PC and features a transparent finish, processed by means of sandblasting; the diffuser is made of pmma with a silk-screening treatment. The ingress protection degree is IP20;

The total absorbed power is 36 W. The power supply cable is included and features.

The device features protection class I and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

#### **Illuminotechnical Features**

Source lumens	3847 lm
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25

#### **LED Life / Failure Ratio**

L80 B20 C0 61000h (at Tj 105 Ta 25 )