LEDS C4

Installation Instructions
3D File
Photometry
Revit (BIM)

Cube Pro 4 LEDS

AN12-P6V8S1DUZ5

Spotlight IP66 Cube Pro 4 LEDS LED 6.2W LED warm-white 2700K DALI-2 Urban grey 647lm



TECHNICAL FEATURES

IP66 IK07 90º

Total power consumption of light (W) : 7.3W

Real lumens : 647

Real lm/W : 89

Correlated Colour Temperature (CCT) : LED warm-white 2700K

Lens / reflector angle : NARROW 8º

UGR : <=16

Structure material : Aluminium

Structure finish : Urban grey

Diffuser material : Glass

Diffuser finish : Transparent

Smart Compatible

- 71-A237-00-00: Casambi

Voltage / frequency : 100-240V/50-60Hz

Dimming protocol : DALI-2

Power Factor : 0.90

Useful life : 50.000h L80B20

Warranty : 5 Years

Resistant to marine environments : Yes

Easily recycled luminaire

LUMINOTECHNIC FEATURES

Lampholder	Quantity	Light source power (W)
LED	1	6.2W





LOGISTICS

Net weight (kg): 1.72

Packaged weight (kg): 1.9

Packaging: 120mm x 120mm x 150mm

8 Un

Image may not match reference