Buonanotte



Table Lamps | 220-240 V | 1xE14 8961



Finishing casing















| | 176 | 166 |
|-----|-----|------|
| 193 | | 0127 |

| Technical data | |
|--|---------------------------|
| Designer | Giovanni Luigi Gorgoni |
| Construction year | 1965 |
| Туре | Table Lamps |
| Installation position | Floor |
| Installation environment | Indoor |
| Power | 1 x 5 W |
| Lamp cap | 1 x E14 |
| Frequency | 50-60 Hz |
| Optics | General Lighting |
| Light emission direction | downward and upward |
| Safety class | 2 |
| IP | IP20 |
| Glow wire test | 850° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| Dimmable article | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | Yes |
| Cable length | 2 m |
| Electric socket | Type L |
| Resin potting | No |
| Net weight | 0.85 Kg |
| - | |

| Material | metal | |
|--------------------|-------------------------|--|
| Colour | Embossed white RAL 9003 | |
| Processing | Coating | |
| | | |
| Finishing diffuser | | |
| Material | metal | |
| Colour | Embossed white RAL 9003 | |
| Processing | Coating | |
| | | |
| Finishing base | | |
| Material | metal | |
| Colour | Embossed white RAL 9003 | |
| Processing | Coating | |

Buonanotte



Table Lamps | 220-240 V | 1xE14 **8961**

Double emission table lamps for indoor application. LED lamplamp included, lamp cap 1xE14.

The device body is made of metal and features a embossed white ral 9003 finish, processed by means of coating; the diffuser is made of metal with a coating treatment. The ingress protection degree is IP20; the total weight is of 0.85 kg.

. The power supply cable is included and features a 2 m lenght.

The device features protection class II and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains a light source of energy efficiency class A+.

| Illuminotechnical Features | | | |
|----------------------------|--------|--|--|
| Source lumens | 470 lm | | |
| Colour temperature | 2700 K | | |
| Colour rendering index | 80 Ra | | |