



Circular Inward ø1200 Recessed

CD5B-00V9AZRUEF

Benedito Design



TECHNICAL FEATURES





Power (W) : 63.5W
 Total power consumption of light (W) : 70W
 Real lumens : 2106
 Real lm/W : 30
 Colour temperature : LED warm-white 2700K
 Lens / reflector angle : HORIZONTAL 104°
 Structure material : Aluminium
 Structure finish : Gold
 Diffuser material : Polycarbonate
 Diffuser finish : Opal
 Useful life : 50.000h L80B20

Equipment included : Yes, electronic
 Brand : MEANWELL
 Voltage / frequency : 100-240V/50-60Hz
 Warranty : 5 Years
 Max. temperature : 25°C
 Energy efficiency : LED A++

LUMINOTECHNIC FEATURES

Light source: LED
 Luminance C0°65°: 437
 Luminance 90°65°: 433
 CRI: 90
 MacAdam steps: 5
 Photobiological risk: RG0
 UGR
 UGR crosswise: 14.5
 UGR lengthwise: 14.5

UGR	
S=0.250	
Ceiling / cavity	0.7
Walls	0.5
Working Plane	0.2
Room dimensions	X=4H, Y=8H
UGR crosswise	14.5
UGR lengthwise	14.5



LOGISTICS

Net weight (kg): 6
 Packaged weight (kg): 13
 Packaging: 1300mm x 1300mm x 150mm

