




Circular Outward ø900 Recessed CF5K-00V9AZOU05

Benedito Design



TECHNICAL FEATURES




Power (W) : 45.6W
 Total power consumption of light (W) : 52W
 Real lumens : 1448
 Real lm/W : 28
 Colour temperature : LED warm-white 2700K
 Structure material : Aluminium
 Structure finish : Metallic black
 Diffuser material : Polycarbonate
 Diffuser finish : Opal
 Useful life : 50.000h L80B20

Equipment included : Yes, electronic
 Brand : MEANWELL
 Voltage / frequency : 100-240V/50-60Hz
 Warranty : 5 Years
 Max. temperature : 25°C
 Energy efficiency : LED A++

LUMINOTECHNIC FEATURES

Light source: LED
 Luminance C0°65°: 480
 Luminance 90°65°: 480
 CRI: 90
 MacAdam steps: 5
 Photobiological risk: RG0
 UGR
 UGR crosswise: 15.1
 UGR lengthwise: 15.1

UGR	
S=0.250	
Ceiling / cavity	0.7
Walls	0.5
Working Plane	0.2
Room dimensions	X=4H, Y=8H
UGR crosswise	15.1
UGR lengthwise	15.1



LOGISTICS

Net weight (kg): 5
 Packaged weight (kg): 10
 Packaging: 1000mm x 1000mm x 100mm

