



Downhill Dan 30





The Downhill Dan 30 extrusion is a versatile and powerful downlighting system. Utilizing up to a 2650 lumen per metre LED strip, the profile is ideal for applications where maximum light output is key. A versatile system suitable for various mounting options, Downhill Dan 30 can be surface mounted, recessed and suspended. Both wire and rod suspension options are available and the cowling accessory for plastered ceilings and walls creates a beautiful trimless finish.

MOUNTING OPTIONS
Surface mounted
Wire suspended
Rod suspended
Recessed
Wall mounted

DIFFUSER OPTIONS
Opal
Clear

SUPER SERIES LED STRIP OPTIONS				
Lumens per metre	Watts per metre	Colour temp		
310lm		2700K		
330lm	3W	3000K		
345lm		4000K		
760lm		2700K		
800lm	7W	3000K		
840lm		4000K		
1520lm		2700K		
1600lm	14W	3000K		
1680lm		4000K		

Lumens per metre	Watts per metre	Colour temp.
1955lm		2700K
2060lm	20W	3000K
2160lm		4000K
2400lm	26W	2700K
2530lm		3000K
2650lm		4000K

- LED strip options vary depending on region please consult your local distributor for more information. Other LED strip options are available on request, including IP54 and IP67.

 All Lumen values refer to the bare LED strip. Losses through diffuser/profile are not represented. Consult photometric data.

 5 year manufacturer's warranty on Super Series & Spec Series LED strip.





JN-ST-12 Straight joiner



JN-90-12 90 degree joiner





CB-60-R-S / CB-60-R-W / CB-60-R-B Cable base 60, recessed



CB-80-SM-S / CB-80-SM-W / CB-80-SM-B Cable base 80, surface mount

NZ

designed

and

made!



SWK-1-1M / SWK-1-2M / SWK-1-4M Wire suspension



SRK-1-S / SRK-1-W / SRK-1-B







ROD-0.5M / ROD-1M / ROD-2M C-30-I Suspension rod - 0.5m, 1m, 2m Recessing cowling



C-30-EC-I Recessing cowling end cap



WB-DD30 Wall bracket



JN-120-12 120 degree joiner



JN-135-12 135 degree joiner

ADDITIONAL INFORMATION

Applications Installation

Light source

Dimmable

Power supply


General downlighting in kitchens, living rooms, dining rooms, reception counters. Interior or exterior (with IP67 rated LED strip).

Materials Extruded aluminium body, polycarbonate diffuser, aluminium or AES end caps. Finish Natural silver anodised or custom powder coat.

LED ribbon strip.

24V DC - remote driver options ranging from 6W up to 320W.

Various options available, please enquire.



Polar curve for 2250 lumen LED strip with opal

