



# Downhill Dan 35





Downhill Dan 35 is a quick-to-install, recessed down-lighter profile. The asymmetric mounting bracket makes this product unique and means that it can be installed with the LED strip already attached. Downhill Dan 35 has plenty of power for a huge range of applications. Silver anodised or white powder coat are standard finish options.

A.A		ш	Nile	<b>EII</b> 1	TIV4		$\overline{a}$	B 10	ni Pa	27	1S	
M	v	w		ш	٧V	511	$\cup$	ы	III.	21)	CV	

## Recessed

## DIFFUSER OPTIONS

Satin

SUPER SERIES LED STRIP OPTIONS							
Lumens per metre	Watts per metre	Colour temp					
310lm		2700K					
330lm	3W	3000K					
345lm		4000K					
760lm		2700K					
800lm	7W	3000K					
840lm		4000K					
1520lm		2700K					
1600lm	14W	3000K					
1680lm		4000K					

Lumens per metre	Watts per metre	Colour temp.		
1955lm		2700K		
2060lm	20W	3000K		
2160lm		4000K		
2400lm		2700K		
2530lm	26W	3000K		
2650lm		4000K		

- LED strip options vary depending on region – please consult your local distributor for more information. Other LED strip options are available on request, including IP54 and IP67.

- All Limen values refer to the bare LED strip. Losses through diffuser/profile are not represented. Consult photometric data.

- 5 year manufacturer's warranty on Super Series & Spec Series LED strip.




JN-ST-23 Straight joiner



JN-90-23 90 degree joiner



MB-DD35 Mounting bracket



SMRB Seismic restraint bracket

### ADDITIONAL INFORMATION

General downlighting in kitchens, living rooms, dining rooms, reception counters, Applications

Interior or exterior (with IP67 rated LED strip). Installation

Extruded aluminium body, PMMA diffuser, aluminium end caps. Materials


Finish Natural silver anodised, Mannex White powder coat or custom powder coat colours.

Light source LED ribbon strip.

Power supply 24V DC - remote driver options ranging from 6W up to 320W.

Dimmable Various options available, please enquire.





Polar curve for 2250 lumen LED strip with satin

