


Richie Rail 20





Richie Rail 20 is a unique illuminated handrail system with a diameter of 42.4mm. Hollow wall brackets conceal the power supply to the LED strip, and the low voltage input makes the handrail safe to touch. The innovative sliding wall brackets allow minimal power feeds to the LED strip for simple installation. Richie Rail 20 is suitable for use on residential and commercial stairs and thoroughfares including accessible routes and exterior urban spaces. Richie Rail 20 can be supplied as a "plug-and-play" modular system, or as a seamless, fully welded system in satin or polished finishes.

MACLIN	ITTINI			O 1	
MOUN	$\Pi \Pi \Pi \Pi$	G O	FIII	\circ	12

Wall mounted Post-top

DIFFUSER OPTIONS

Opal		
Clear		

SUPER SERIES LED STRIP OPTIONS

Lumens per metre	watts per metre	Cotour terrip.
310lm		2700K
330lm	3W	3000K
345lm		4000K
760lm		2700K
800lm	7W	3000K
840lm		4000K
1520lm		2700K
1600lm	14W	3000K
1680lm		4000K

Lumens per metre. Watts per metre. Colour temp

- LED strip options vary depending on region - please consult your local - LED strip options vary depending on region – piease consult your own distributor for more information. Other LED strip options are available on request, including IP67 and RGBW colour change. - All lumen values refer to the bare LED strip. Losses through diffuser/ profile are not represented. Consult photometric data. - 5 year manufacturer's warranty on Super Series LED strip.



WBRR-SS (satin finish) or WBRR-POL (polished finish)



JN-VU-RR20-SS (satin finish) or Variable joiner, up




HR-RR20-SS (satin finish) or HR-RR20-POL (nolished finish) Handrail. 316 stainless steel





JN-TUBE-20-SS (satin finish) or JN-TUBE-20-POL (polished finish) Joiner tube, for welded systems only



EX-RR20-MSA



JN-90-RR20-W-SS (satin finish) 90 degree joiner tube, for welded systems only




EC-RR20-SS (satin finish) or EC-RR20-POL (polished finish) Handrail end cap



JN-180-RR20-W-SS (satin finish) 180 degree joiner tube, for welded systems only



JN-ST-RR20-SS (satin finish) or



EC-TUBE-20-SS (satin finish) EC-TUBE-20-POL (polished finish) End cap for blank tube, for welded systems only



JN-90-RR20-SS (satin finish) or



Straight joiner

3N-51-RR20-POL (polished finish)
Straight joiner

3N-50-RR20-POL (polished finish)
90 degree joiner



JN-VD-RR20-SS (satin finish) or Variable ioiner de



PTBRR-SS (satin finish) or PTBRR-POL (polished finish) Post top bracket



GMBRR-SS (satin finish) Glass mount bracket

ADDITIONAL INFORMATION

Applications Commercial stairs, public stairs, accessible routes, exterior urban spaces.

Installation Interior or exterior (with IP67 rated LED strip).

Materials 316 stainless steel rail and components, extruded aluminium, polycarbonate diffuser.

Finish Satin or polished 316 stainless steel.

Light source LED ribbon strip.

24V DC - remote driver options ranging from 6W up to 320W. Power supply

Dimmable Various options available, please enquire.



