



Sideways Sally 20C





The Sideways Sally 20C extrusion is a compact uplight/downlight solution providing powerful LED lighting. A versatile system suitable for various mounting options, Sideways Sally 20C can be surface mounted, wall mounted and suspended. The concealed mounting clip provides a quick and secure fixing to joinery. Both wire and rod suspension options are available for the Sideways Sally 20C extrusion.

| MOUN | HNG | OPI | IONS |
|---------|------|------|------|
| | | | |
| Surface | moul | ntad | |

| Surface mounted | |
|-----------------|--|
| Rod suspended | |
| Wire suspended | |
| Wall mounted | |

DIFFUSER OPTIONS

SUPER SERIES LED STRIP OPTIONS

| Lumens | per metre | watts per metre | Colour temp. |
|--------|-----------|-----------------|--------------|
| 310lm | | | 2700K |
| 330lm | | 3W | 3000K |
| 345lm | | | 4000K |
| 760lm | | | 2700K |
| 800lm | | 7W | 3000K |
| 840lm | | | 4000K |
| 1520lm | | | 2700K |
| 1600lm | | 14W | 3000K |
| 1680lm | ' | | 4000K |
| | | | |

- LED strip options vary depending on region – please consult your local distributor for more information. Other LED strip options are available on request, including IPS4 and IP67.

- All lumen values refer to the bare LED strip. Losses through diffuser/profile are not represented. Consult photometric data.

- 5 year manufacturer's warranty on Super Series & Spec Series LED strip.

ACCESSORIES



JMC-12 Joinery mounting clip



JN-ST-12



JN-90-12 90 degree joiner



CB-60-R-S / CB-60-R-W / CB-60-R-B



CB-80-SM-S / CB-80-SM-W / CB-80-SM-B Cable base 80, surface mount



SWK-1-1M / SWK-1-2M / SWK-1-4M Wire suspension



SRK-1-S / SRK-1-W / SRK-1-B



SRK-6-S / SRK-6-W / SRK-6-B





ROD-0.5M / ROD-1M / ROD-2M WB-SS20 Suspension rod - 0.5m, 1m, 2m Wall bracket



JN-120-12 120 degree joiner



JN-135-12 135 degree joiner

ADDITIONAL INFORMATION

Task lighting over kitchen islands or reception counters, mirror lighting **Applications**

Installation Interior or exterior (with IP67 rated LED strip).

Extruded aluminium body, PMMA diffuser, aluminium end caps. Materials


Finish Natural silver anodised or custom powder coat.

Light source LED ribbon strip.

24V DC - remote driver options ranging from 6W up to 320W. Power supply

Dimmable Various options available, please enquire.





Polar curve for 1890 lumen LED strip with satin

