


Mr.Magoo_S



Ceiling Lights | 220-240 V
104 topLED 23 W DC - 23 W AC | CRI 90
8006N



Technical data	
Construction year	2017
Type	Surface
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward
Power	23 W
Source lumens	2914 lm
Frequency	50 - 60 Hz
CCT / Tone	4000 K
Colour rendering index	90 Ra
C.C. / C.V.	AC
Safety class	1
IP	IP40
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	DALI
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Double emission
Net weight	2.54 Kg
Electrostatic discharge protection	No
Surge protection	No

Finishing casing	
Material	Aluminium
Colour	white
Processing	Coating

Finishing diffuser	
Material	PE
Colour	neutral



Ceiling Lights | 220-240 V | 104 topLED 23 W DC - 23 W AC | CRI 90 | Base 8006N

Double emission ceiling lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 104 topLED LEDs with CCT of 4000 K and a CRI 90; the source luminous flux is 2914 lm, with a 126.7 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a white finish, processed by means of coating; the diffuser is made of pe. The ingress protection degree is IP40; the total weight is of 2.54 kg.

The total absorbed power is 23 W.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features

Light Output Ratio (LOR)	62 %
Source lumens	2914 lm
Delivered lumens	1820 lm
Consumption	23 W
Luminaire efficacy	79 lm/W
Colour temperature	4000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25

LED Life / Failure Ratio


L80 B20 C0 80h

UGR

UGR axial	14.8
UGR transversal	15.8
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

Light distribution simmetry	Symmetrical 2
C0/C180 optics	117°
C90/C270 optics	110°



Distance [m]	Cone diameter [m]	illuminance [lx]
0.5	1.42 1.64	E(0°) 2011 E(C90) 193 E(C0) 142
1.0	2.84 3.28	E(0°) 503 E(C90) 48 E(C0) 36
1.5	4.25 4.91	E(0°) 223 E(C90) 21 E(C0) 16
2.0	5.67 6.55	E(0°) 126 E(C90) 12 E(C0) 9
2.5	7.09 8.19	E(0°) 80 E(C90) 8 E(C0) 6
3.0	8.51 9.83	E(0°) 56 E(C90) 5 E(C0) 4

Distance [m] Cone diameter [m] illuminance [lx]

— C0/C180 (Half-peak divergence: 117.2°)
— C90/C270 (Half-peak divergence: 109.6°)